



WI-MATIC ATC300E

NEW**230V****24V****i227**

Electromechanical operator for windows with double layer chain, ideal for outward-opening windows.



| TECHNICAL FEATURES | 230V | 24V |
|-------------------------|--|--|
| POWER SUPPLY | 100-240 Vca 50/60 Hz | 24V dc |
| ABSORBED CURRENT | 0.25 A | 1.0 A |
| RATED POWER | 28W (PEAK 40W) | 28W (PEAK 40W) |
| PUSH/PULL FORCE | 250 N | 250 N |
| SPEED | 10 mm/s | 10 mm/s |
| ADJUSTABLE STROKES FROM | 100-400 mm | 100-400 mm |
| TEMPERATURE | -20°+50° | -20°+60° |
| SIZE OPERATOR | (LxHxP) 460 x 42 x 56 mm | (LxHxP) 460 x 42 x 56 mm |
| SIZE WINDOWS | 1600 mm MAX | 1600 mm MAX |
| IP CLASS | IP43 | IP42 |
| PARALLEL CONNECTION | Yes, with 1 motor for each frame. Max 15-20 motors can be connected together | Yes, with 1 motor for each frame. Max 15-20 motors can be connected together |
| OPERATOR WEIGHT | 1.6 KG | 1.6 KG |



Wide voltage 100-240Vca power input,
suitable for all country's different requests.

Rocker brackets for long runs even on small frames. They also allow the operator suitable to a wide range of applications.

The stroke is easily adjusted through a simple rotation from the outside of the operator so you don't need to open anything.

Adjustable running, from 100 up to 400mm

Double layers stainless metal chain
alloy steel that ensure maximum strength.

Very smooth running
Applications bottom hinged or roof-domes bracket available separately.

Slim dimensions and compact shape

make this product easy to integrate with the window frame regardless of its thickness or design.



Aluminum casing with oxidation treatment satin to give maximum strength and aesthetics. Operator quiet thanks to the extremely robust structure that prevents vibration.

Special surface treatment to give an excellent resistance to oxidation. Excellent finishes too.

Available also the model to 24V low tension.

| ITEM NUMBER | DESCRIPTION | STROKE mm | POWER SUPPLY |
|----------------------|---|-----------|--------------|
| 43509/017 | WI-MATIC ATC300E with bracket for outward-opening applications and bracket for roof-domes windows application included. | 400 mm | 230 Vca |
| NEW 43509/024 | WI-MATIC ATC300E 24V with bracket for outward-opening applications and bracket for roof-domes windows application included. | 400 mm | 24 Vdc |

ACCESSORIES

| | ITEM NUMBER | DESCRIPTION | | |
|---|-------------|---|---|---|
|  | 43509/050 | Bottom hinged bracket | - | - |
|  | 43509/051 | Bracket fixing motor (already included into the Wi-Matic product) | - | - |