SC956A4C0

Hyde Park, Ultrasonic sensor, analog, current (mA), 30 mm barrel, 15 24 V DC

Main

Range of product	Hyde Park
Sensor type	Ultrasonic sensor
Series name	Superprox +
Device short name	SC956
Sensor design	Cylindrical M30
Type of sensing window	Adjustable
Material	Plastic
Enclosure material	ULTEM
Front material	Silicone rubber
Type of output signal	Analog
ISO thread	M30 x 1.5
Wiring technique	4-wire
[Us] rated supply voltage	1524 V DC with overload and short-circuit protection
Supply voltage limits	1328 V DC
Analogue output range	420 mA configurable
Electrical connection	Male connector M12 4 pins
Product specific application	Analog output

Complementary

[Sn] nominal sensing distance	2 m	
[Sd] sensing range	0.122 m	
Maximum differential travel	2.5 mm	
Blind zone	120 mm	
Transmission frequency	200 kHz	
Repeat accuracy	0.9 %	
Beam angle	10 °	
Minimum size of detected object	Cylinder diameter 1.6 mm - up to 305 mm sensing distance	
Current consumption	80 mA	
Maximum switching current	60 mA with reverse polarity protection	
Height	30 mm	
Width	34.7 mm	
Depth	30 mm	
Length	96 mm	
Net weight	0.9 kg	

Environment

Product certifications	UL	
Marking	CE	
NEMA degree of protection	NEMA 4X (indoor use only)	
IP degree of protection	IP67	
Ambient air temperature for operation	050 °C	
Ambient air temperature for storage	-2080 °C	
Relative humidity	100 % without condensation	
Vibration resistance	+/-1 mm conforming to IEC 60068-2-6 (f = 1055 Hz)	
Shock resistance	30 gn in all 3 axes for 11 ms conforming to IEC 60068-2-27	

Resistance to electromagnetic fields	10 V/m level 3 conforming to IEC 61000-4-3
Resistance to fast transients	1 kV level 3 conforming to IEC 61000-4-4
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com
Contractual warranty	
Warranty	18 months